

AAPKE SAFAR KA BHAROSEMAND SAATHI

Jisme kharcha kum munafa jyada

TATA ACE GOLD



*Available in Petrol, Diesel & CNG

BS6 P2>>>
Phase2 Ready

*T&C apply



**Low
TCO***



**High
Mileage***



**Low
Maintenance**

TATA **ACE GOLD** PETROL

694 cc E20 FUEL
COMPLIANT ENGINE

MORE
POWER WITH
**2 CYLINDER
ENGINE**

TATA **ACE GOLD** DIESEL

702 cc TURBO CHARGED
INTER COOLED ENGINE



MORE
SAFETY



BIGGER HEAD LAMPS

MORE
COMFORT



SEATS WITH HEADRESTS

BETTER
DRIVABILITY



NEW STEERING

IMPROVED
CONTROL



DIRECT DRIVE GEARBOX

LONG RANGE
UPTO 400 km*
with _____
105 litres (18kg)
CNG TANK

TATA ACE GOLD CNG+

694 cc ENGINE



MORE
SAFETY



BIGGER HEAD LAMPS

MORE
COMFORT



SEATS WITH HEADRESTS

BETTER
DRIVABILITY



NEW STEERING

LONG
LOAD BODY



2 520 mm (8.2 ft.)

Features	Ace Gold Diesel BS6	Ace Gold Petrol BS6 CLB, CAB CHASSIS, HIGH DECK	Ace Gold CNG + Ace Gold CNG BS6
Engine	2 cylinder 702 cc Compression Ignition DI	2 cylinder 694 cc MPFI BS-VI RDE, 4 Stroke Water cooled	2 cylinder Positive Ignition, Four Stroke, Naturally Aspirated, DI
Engine Capacity	702 cc	694 cc	694 cc
Max Power	Power Mode : 16.17 kW @ 3 600 +/-100 r/min City Mode : 12.5 kW at 3 600 +/-100 r/min	22.1kW (30 Ps) @ 4 000 r/min	19.4 kW @4000 (+/-100) r/min
Max Torque	Power Mode : 55 Nm @ 1 800 to 2 200 engine r/min; City Mode : 40 Nm @1 800 to 2 200 engine r/min	55 Nm @ 2 500 - 3 000 r/min	51 Nm @ 2 000 - 2500 r/min
Max Gradeability	For Power Mode - 14.5 degree & For City Mode - 12.5 degree	14 degree	13.5 degree
Gearbox	DIRECT DRIVE GBS G65-5/6.31	DIRECT DRIVE GBS 65- 5/6.31	GBS 65- 5/5.6
Clutch	Single plate dry friction diaphragm type	Single plate dry friction diaphragm type	Single plate dry friction diaphragm type
Steering	Manual Steering System 27.9-30.4(Variable); 380 mm diameter	mechanical variable ratio (27.9 to 30.4) Variable, 380 mm diameter	Manual. 27.9-30.4(variable ratio); 380mm diameter
Max Speed	65 km/h	65 km/h	70 km/h
Brakes	Front - Disc brakes; Rear - Drum brakes	Front - Disc brakes Rear - Drum brakes	Front - Disc brakes; Rear - Drum brakes
Suspension Front	Rigid Axle with Parabolic Leaf Spring	Rigid Axle with Parabolic Leaf Spring	Rigid Axle with Parabolic Leaf Spring
Suspension Rear	Live Axle with semi-elliptical Leaf Spring	Live Axle with semi-elliptical Leaf Spring	Live Axle with semi-elliptical Leaf Spring
Tyres	145 R12 LT 86/84 R 8PR	145/80 R12 LT 86/84 Q 8PR RADIAL TUBELESS	145/80 R12 LT 86/84 Q 8PR RADIAL TUBELESS
Fuel Tank Capacity	30 L	26 L	CNG+ : CNG Capacity : 18 kg Water Capacity : 105L (35L + 35L + 35L) CNG : CNG Capacity : 12 kg Water Capacity : 70L (35L + 35L)
Dimensions			
Length (mm)	3 800	3 800	4 075
Width (mm)	1 500	1 500	1 500
Height (mm)	1 845	1 840 (High Deck : 1945)	1 840
Wheelbase (mm)	2 100	2 100	2 250
Ground Clearance (mm)	160	160	160
Cargo Box Dimensions (mm)	2 200 X 1 490 X 300	CLB : 2 200 X 1 490 X 300 HIGH DECK : 2 200 X 1 490 X 1 205	2520 X 1490 X 300
Min TCR (mm)	4 300	4 300	4 625
Weight			
Max GVW (kg)	1 685	1 615	1 630
Kerb Weight (kg)	935	CLB:840 CAB CHASSIS : 740 HIGH DECK : 880	CNG + : 1015 CNG : 970
Payload (kg)	750	CLB:775 HIGH DECK : 735	CNG+ : 615 CNG : 660
DEF Tank	12.5 L	NA	NA
Warranty	2 years / 72 000 km	2 years / 72 000 km	2 years / 72 000 km